

DWT6 4'-750 COMPARTMENT
754 Gallons

06/22/2023

DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)
1/8	1	6 1/8	56	12 1/8	150	18 1/8	264
1/4	1	6 1/4	58	12 1/4	152	18 1/4	266
3/8	2	6 3/8	60	12 3/8	155	18 3/8	269
1/2	2	6 1/2	61	12 1/2	157	18 1/2	271
5/8	3	6 5/8	63	12 5/8	159	18 5/8	274
3/4	4	6 3/4	65	12 3/4	161	18 3/4	276
7/8	4	6 7/8	66	12 7/8	163	18 7/8	279
1	5	7	68	13	166	19	281
1 1/8	6	7 1/8	70	13 1/8	168	19 1/8	284
1 1/4	7	7 1/4	72	13 1/4	170	19 1/4	286
1 3/8	7	7 3/8	74	13 3/8	173	19 3/8	289
1 1/2	8	7 1/2	75	13 1/2	175	19 1/2	291
1 5/8	9	7 5/8	77	13 5/8	177	19 5/8	294
1 3/4	10	7 3/4	79	13 3/4	179	19 3/4	296
1 7/8	11	7 7/8	81	13 7/8	182	19 7/8	299
2	12	8	83	14	184	20	301
2 1/8	13	8 1/8	85	14 1/8	186	20 1/8	304
2 1/4	14	8 1/4	86	14 1/4	189	20 1/4	307
2 3/8	15	8 3/8	88	14 3/8	191	20 3/8	309
2 1/2	16	8 1/2	90	14 1/2	193	20 1/2	312
2 5/8	17	8 5/8	92	14 5/8	196	20 5/8	314
2 3/4	18	8 3/4	94	14 3/4	198	20 3/4	317
2 7/8	19	8 7/8	96	14 7/8	200	20 7/8	319
3	21	9	98	15	203	21	322
3 1/8	22	9 1/8	100	15 1/8	205	21 1/8	324
3 1/4	23	9 1/4	102	15 1/4	208	21 1/4	327
3 3/8	24	9 3/8	104	15 3/8	210	21 3/8	330
3 1/2	26	9 1/2	106	15 1/2	212	21 1/2	332
3 5/8	27	9 5/8	108	15 5/8	215	21 5/8	335
3 3/4	28	9 3/4	110	15 3/4	217	21 3/4	337
3 7/8	29	9 7/8	112	15 7/8	220	21 7/8	340
4	31	10	114	16	222	22	342
4 1/8	32	10 1/8	116	16 1/8	224	22 1/8	345
4 1/4	33	10 1/4	118	16 1/4	227	22 1/4	348
4 3/8	35	10 3/8	120	16 3/8	229	22 3/8	350
4 1/2	36	10 1/2	122	16 1/2	232	22 1/2	353
4 5/8	38	10 5/8	124	16 5/8	234	22 5/8	355
4 3/4	39	10 3/4	126	16 3/4	237	22 3/4	358
4 7/8	41	10 7/8	128	16 7/8	239	22 7/8	360
5	42	11	131	17	241	23	363
5 1/8	44	11 1/8	133	17 1/8	244	23 1/8	366
5 1/4	45	11 1/4	135	17 1/4	246	23 1/4	368
5 3/8	47	11 3/8	137	17 3/8	249	23 3/8	371
5 1/2	48	11 1/2	139	17 1/2	251	23 1/2	373
5 5/8	50	11 5/8	141	17 5/8	254	23 5/8	376
5 3/4	51	11 3/4	144	17 3/4	256	23 3/4	378
5 7/8	53	11 7/8	146	17 7/8	259	23 7/8	381
6	55	12	148	18	261	24	384

DWT6 4'-750 COMPARTMENT
754 Gallons

06/22/2023

DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)
24 1/8	386	30 1/8	508	36 1/8	619	42 1/8	709
24 1/4	389	30 1/4	510	36 1/4	622	42 1/4	711
24 3/8	391	30 3/8	513	36 3/8	624	42 3/8	712
24 1/2	394	30 1/2	515	36 1/2	626	42 1/2	714
24 5/8	396	30 5/8	518	36 5/8	628	42 5/8	715
24 3/4	399	30 3/4	520	36 3/4	630	42 3/4	717
24 7/8	402	30 7/8	523	36 7/8	632	42 7/8	718
25	404	31	525	37	634	43	719
25 1/8	407	31 1/8	528	37 1/8	636	43 1/8	721
25 1/4	409	31 1/4	530	37 1/4	638	43 1/4	722
25 3/8	412	31 3/8	532	37 3/8	640	43 3/8	724
25 1/2	414	31 1/2	535	37 1/2	642	43 1/2	725
25 5/8	417	31 5/8	537	37 5/8	644	43 5/8	726
25 3/4	420	31 3/4	540	37 3/4	646	43 3/4	728
25 7/8	422	31 7/8	542	37 7/8	648	43 7/8	729
26	425	32	544	38	650	44	730
26 1/8	427	32 1/8	547	38 1/8	652	44 1/8	731
26 1/4	430	32 1/4	549	38 1/4	654	44 1/4	733
26 3/8	432	32 3/8	552	38 3/8	656	44 3/8	734
26 1/2	435	32 1/2	554	38 1/2	658	44 1/2	735
26 5/8	438	32 5/8	556	38 5/8	660	44 5/8	736
26 3/4	440	32 3/4	559	38 3/4	662	44 3/4	737
26 7/8	443	32 7/8	561	38 7/8	664	44 7/8	738
27	445	33	563	39	666	45	739
27 1/8	448	33 1/8	566	39 1/8	668	45 1/8	740
27 1/4	450	33 1/4	568	39 1/4	670	45 1/4	741
27 3/8	453	33 3/8	570	39 3/8	672	45 3/8	742
27 1/2	455	33 1/2	573	39 1/2	673	45 1/2	743
27 5/8	458	33 5/8	575	39 5/8	675	45 5/8	744
27 3/4	460	33 3/4	577	39 3/4	677	45 3/4	745
27 7/8	463	33 7/8	579	39 7/8	679	45 7/8	746
28	465	34	582	40	681	46	747
28 1/8	468	34 1/8	584	40 1/8	683	46 1/8	748
28 1/4	471	34 1/4	586	40 1/4	684	46 1/4	749
28 3/8	473	34 3/8	589	40 3/8	686	46 3/8	749
28 1/2	476	34 1/2	591	40 1/2	688	46 1/2	750
28 5/8	478	34 5/8	593	40 5/8	690	46 5/8	751
28 3/4	481	34 3/4	595	40 3/4	691	46 3/4	751
28 7/8	483	34 7/8	598	40 7/8	693	46 7/8	752
29	486	35	600	41	695	47	752
29 1/8	488	35 1/8	602	41 1/8	696	47 1/8	753
29 1/4	491	35 1/4	604	41 1/4	698	47 1/4	753
29 3/8	493	35 3/8	606	41 3/8	700	47 3/8	754
29 1/2	496	35 1/2	609	41 1/2	701	47 1/2	754
29 5/8	498	35 5/8	611	41 5/8	703	47 5/8	754
29 3/4	501	35 3/4	613	41 3/4	704		
29 7/8	503	35 7/8	615	41 7/8	706		
30	505	36	617	42	708		

Fiber Glass Systems



HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. However, some water detection paste cannot detect antifreeze mixtures. If antifreeze mixtures are used for the cavity monitoring fluid, the following product is capable of detecting water or antifreeze (brine or up to 50 percent glycol) solution in the tank water bottoms:

Kolor Kut Water Finding Paste Description - PASTE02 - for Salt and Chloride Solutions
7915 East Elm Street
Houston, TX 77012
Phone (713) 926-4780
E-Mail Sales@KolorKut.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.

NOV - Fiber Glass Systems - Containment Solutions™ Tanks

500 Conroe Park Drive West
Conroe, TX 77303
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 5/16" deflector plate.